

→ **Especially recommended for the requirements of an equine practice**

### Brief description

- Battery operated HF X-ray unit with pulse-frequency modulation
- Total weight: 6800 g (battery included)
- Operator-friendly due to a centered balance point
- Innovative impact resistant construction
- DR interface for the connection with digital systems
- Latest Toshiba tube up to 90kV
- High Power mode (HP)
- Technology meets the radiation protection standards of tomorrow already today
- Activation of collimator light by hand switch
- Collimator including format pre-adjustment, dual laser pointer and spirit level
- Digital display and adjustment of mAs, sec., kV
- Display of battery charging status
- High-capacity Li-ion battery for about 300 exposures per charging
- Charging time: 240 minutes
- LED display "X-RAY", "READY" and "ERROR"
- 5 memory buttons
- Acoustic and optic signal during exposure

## GIERTH TR 90/20 *Battery* - Battery operated - new design - maximum power

### Specifications

**Construction:** battery operated, pulse-frequency modulation high frequency generator impact resistant construction

**Output in 2-kV steps:**  
 40-60 kV = 20 mA (max.)  
 62-80 kV = 15 mA (max.)  
 82-90 kV = 10 mA (max.)  
 82-90 kV = 15 mA (max. HP mode)

**X-ray tube:** Toshiba D-0814  
**Focus:** 0.8 mm  
**Timer:** digital, from 0.01-1.0 sec.  
**Total filtration:** 2.7 mm Al (incl. collimator)

**Inverter frequency:** 100 kHz, full bridge inverter system

**Power requirement:** 1.35 kVA

**Dual laser pointer:** 2 x class IIIa laser diodes, 12V DC

**Serial interface:** DR RJ45 connector

**Weight:** 6.8 kg incl. collimator, dual laser and battery

**Dimensions:** L 265 mm, W 220 mm, H 180 mm

### Battery:

**Battery model:** Lithium-ion battery

**Charging time:** 240 minutes

**Line voltage :** AC single phase, 130-260 V, 50/60 kHz



- battery operated, lightweight X-ray unit (only 6800 g)
- the completely charged battery allows about 300 exposures

**GIERTH TR 90/20 Battery** - Battery operated  
- new design - maximum power

TR 90/20 Battery



Battery charger with battery



**Specifications subject to revision without notice**

Specifications subject to revision without notice  
The editor strives to impart correct and up to date information. The provided specifications are based on current knowledge and are subject to revision without notice. This brochure is subject to correction. The editor assumes no responsibility for the information being up to date, correct and complete.  
All furnished logos, pictures and graphics are property of the particular company and subject to copyright of the licensor. Use, dissemination, distribution or copying of the pictures, logos or text compiled or processed by the editor is subject to our written consent. All rights reserved.



Stamp of distribution partner

For further questions please contact us directly:



**GIERTH X-Ray international GmbH**

Am Südspeicher 4, 01587 Riesa

**Hotline: + 49 (0) 3525 - 51 24 59**

**E-mail: [info@gierth-x-ray.de](mailto:info@gierth-x-ray.de)**

